

ECOBLUE RY22

- Compared to standard product, rolling resistance is decreased 20% and fuel consumption is decreased 3%
- Wear resistance increases 15% by the help of deepen pattern and special formulation.
- The design of 4 directional grooves and full broadwise grooves provides ultra braking, diversion and drainage performance.
- Advanced pattern and structure design offers low noise levels performance.

Series	Size	LI	SS	Std.Rim	Section Width(mm)	Overall Diameter(mm)	Max. Load		Max.Pressure		Labeling		
							kgs	lbs	kpa	psi	R	W	LV
50	215/50R17 XL	95	V	7	226	648	690	1521	340	50	E	B	70 2
	225/50R17	94	V	7	233	658	670	1477	350	51	E	B	70 2
55	205/55R16	91	V	6.5	214	632	615	1356	350	51	E	B	70 2
	235/55R18	100	V	7.5	245	715	800	1764	350	51	E	B	70 2
60	195/60R15	88	H	6	201	615	560	1235	350	51	E	B	70 2
	205/60R16	92	V	6	209	652	630	1389	350	51	E	B	70 2
	215/60R16	95	V	6.5	221	664	690	1521	350	51	E	B	70 2
	225/60R16	98	H	6.5	228	676	750	1653	350	51	E	B	70 2
65	185/65R14	86	H	5.5	189	596	530	1168	350	51	E	B	70 2
	195/65R15	91	H	6	201	635	615	1356	350	51	E	B	70 2
	205/65R15 XL	99	T	6	209	647	775	1709	340	50	E	B	70 2
	215/65R16	98	H	6.5	221	686	750	1653	350	51	E	B	70 2
	225/65R17	102	H	6.5	228	724	850	1874	350	51	E	B	70 2
70	175/70R13	82	T	5	177	576	475	1047	350	51	E	B	70 2
	195/70R14	91	T	6	201	630	615	1356	350	51	E	B	70 2
	205/70R15	96	T	6	209	669	710	1565	350	51	E	B	70 2
	215/70R15	98	T	6.5	221	683	750	1653	350	51	E	B	70 2

UTQG Treadwear 560 Traction A Temperature A

ECOBLUE
RY22

**STRENGTH
POWER
DURABILITY**

ECOBLUE RY26



ECOBLUE RY26

- Asymmetrical pattern design provides superior precision control and drive stability.
- Intensive pattern offers low noise levels and rolling resistance.
- White carbon formula provides better grip.

Series	Size	LI	SS	Std.Rim	Section Width(mm)	Overall Diameter(mm)	Max. Load		Max.Pressure		UTQG		
							kgs	lbs	kpa	psi	Treadwear	Traction	Temperature
40	165/40R16 XL	70	V	6.0	170	538	335	739	340	50	400	A	A
45	165/45R16 XL	74	V	5.5	165	554	335	739	350	51	400	A	A
50	165/50R15	72	V	5.0	170	547	355	783	350	51	400	A	A
55	155/55R14	69	H	5.0	162	526	328	723	350	51	400	A	A
	165/55R14	72	H	5.0	170	538	355	783	350	51	400	A	A
	165/55R15	75	V	5.0	170	563	387	853	350	51	400	A	A
	185/55R15	82	V	6.0	194	585	475	1047	350	51	400	A	A
60	165/60R14	75	H	5.0	170	554	387	853	350	51	400	A	A
	185/60R14	82	H	5.5	189	578	475	1047	350	51	400	A	A
	185/60R15	84	H	5.5	189	603	500	1102	350	51	400	A	A
65	175/65R14	82	T/H	5.0	177	584	475	1047	350	51	400	A	A
	185/65R14	86	H	5.5	189	596	530	1168	350	51	400	A	A
	175/65R15	84	H	5.0	177	609	500	1102	350	51	400	A	A
	185/65R15	88	H	5.5	189	621	560	1235	350	51	400	A	A
70	165/70R13	79	T	5.0	170	562	437	963	350	51	400	A	A
	175/70R13	82	T	5.0	177	576	475	1047	350	51	400	A	A
	185/70R13	86	T	5.5	189	590	530	1168	350	51	400	A	A
	165/70R14	81	T	5.0	170	588	462	1019	350	51	400	A	A
	175/70R14	84	T	5.0	177	602	500	1102	350	51	400	A	A

**STRENGTH
POWER
DURABILITY**

ECOBLUE RY26+



ECOBLUE RY26+

- Asymmetrical pattern design provides superior precision control and drive stability.
- Intensive pattern offers low noise levels and rolling resistance.
- White carbon formula provides better grip.

Series	Size	LI	SS	Std.Rim	Section Width(mm)	Overall Diameter(mm)	Max. Load		Max.Pressure		UTQG		
							kgs	lbs	kpa	psi	Treadwear	Traction	Temperature
40	205/40R17 XL	84	W	7.5	212	596	450	992	340	51	400	A	A
45	205/45R16	83	V	7.0	206	590	487	1074	350	51	400	A	A
50	195/50R15	82	V	6.0	201	577	475	1047	350	51	400	A	A
	205/50R16	87	V	6.5	214	612	545	1201	350	51	400	A	A
55	195/55R15	85	V	6.0	201	595	515	1135	350	51	400	A	A
	195/55R16 XL	91	V	6.0	201	620	545	1201	350	51	400	A	A
	205/55R16	91	V	6.5	214	632	615	1356	350	51	400	A	A
60	195/60R15	88	H/V	6.0	201	615	560	1235	350	51	400	A	A
	205/60R15	91	V	6.0	209	627	615	1356	350	51	400	A	A
	205/60R16	92	H	6.0	209	652	630	1389	350	51	400	A	A
	215/60R16	95	V	6.5	221	664	690	1521	350	51	400	A	A
	225/60R16	98	H	6.5	228	676	750	1653	350	51	400	A	A
65	195/65R15	91	V	6.0	201	635	615	1356	350	51	400	A	A
	205/65R15	94	H	6.0	209	647	670	1477	350	51	400	A	A
70	195/70R14	91	T	6.0	201	630	615	1356	350	51	400	A	A

**STRENGTH
POWER
DURABILITY**

VELOCITY RY33



VELOCITY RY33

- Noise reduction is applied to minimise noise levels to 3db and further improve driving performance.
- Asymmetrical pattern design provides superior precision control in both wet and dry conditons.
- Silicon material provides ultra braking, diversion and drainage performance.
- Special design protects the rim of wheel.

Series	Size	LI	SS	Std.Rim	Section Width(mm)	Overall Diameter(mm)	Max. Load		Max.Pressure		Labeling		
							kgs	lbs	kpa	psi	R	W	LV
30	265/30R19 XL	93	Y	9.5	271	643	650	1433	340	50	C	C	70 2
	275/30R19 XL	96	Y	9.5	278	649	710	1565	340	50	C	C	70 2
35	255/35R18 XL	94	Y	9	260	635	670	1477	340	50	C	C	70 2
	265/35R18 XL	97	Y	9.5	271	643	730	1609	340	50	C	C	70 2
	215/35R19 XL	85	Y	7.5	218	633	515	1135	340	50	C	C	70 2
	225/35R19 XL	88	Y	8	230	641	560	1235	340	50	C	C	70 2
	235/35R19 XL	91	Y	8.5	241	674	615	1356	340	50	C	C	70 2
	245/35R19 XL	93	Y	8.5	248	655	650	1433	340	50	C	C	70 2
	225/35R20 XL	90	Y	8	230	666	600	1323	340	50	C	C	70 2
	245/35R20 XL	95	Y	8.5	248	680	690	1521	340	50	C	C	70 2
40	255/35R20 XL	97	Y	9	260	686	730	1609	340	50	C	C	70 2
	205/40R17 XL	84	W	7.5	212	596	500	1102	340	50	C	C	70 2
	255/40R17 XL	98	W	9	260	636	750	1653	340	50	C	C	70 2
	215/40R18 XL	89	W	7.5	218	629	580	1279	340	50	C	C	70 2
	225/40R18 XL	92	W	8	230	637	630	1389	340	50	C	C	70 2
	235/40R18 XL	95	W	8.5	241	645	690	1521	340	50	C	C	70 2
	245/40R18 XL	97	W	8.5	248	653	730	1609	340	50	C	C	70 2
	245/40R19 XL	98	W	8.5	248	679	750	1653	340	50	C	C	70 2
45	255/40R19 XL	100	W	9	260	687	800	1764	340	50	C	C	70 2
	275/40R20 XL	106	W	9.5	278	728	950	2094	340	50	C	C	70 2
	215/45R17 XL	91	W	7	213	626	615	1356	340	50	C	C	70 2
	225/45R17 XL	94	W	7.5	225	634	670	1477	340	50	C	C	70 2
	235/45R17 XL	97	W	8	236	644	730	1609	340	50	C	C	70 2
	245/45R17 XL	99	W	8	243	652	775	1709	340	50	C	C	70 2
	225/45R18 XL	95	W	7.5	225	659	690	1521	340	50	C	C	70 2
	245/45R18 XL	100	W	8	243	677	800	1764	340	50	C	C	70 2
50	255/45R18 XL	103	W	8.5	255	687	875	1929	340	50	C	C	70 2
	255/45R19 XL	104	W	8.5	255	713	900	1984	340	50	C	C	70 2
	245/45R20	99	W	8	243	728	775	1709	350	51	C	C	70 2
	205/50R17 XL	93	W	6.5	214	638	650	1433	340	50	C	C	70 2
	225/50R17 XL	98	W	7	233	658	750	1653	340	50	C	C	70 2
	235/50R18 XL	101	W	7.5	245	693	825	1819	340	50	C	C	70 2
	205/55R16	91	W	6.5	214	632	615	1356	350	51	C	C	70 2
	215/55R16 XL	97	W	7	226	642	730	1609	340	50	C	C	70 2
55	235/55R17 XL	103	W	7.5	245	690	875	1929	340	50	C	C	70 2

UTQG Treadwear 500 Traction A Temperature A

SURETREK RY86

- Streamlined pattern design provides ultra drainage performance and low noise levels.
- Updated belt design offers ride comfort and superior precision control.
- Silicon material specialises in superior wet and dry handling.
- Special design protects the rim of wheel.

Series	Size	LI	SS	Std.Rim	Section Width(mm)	Overall Diameter(mm)	Max. Load		Max.Pressure		Labeling		
							kgs	lbs	kpa	psi	R	W	LV
30	245/30R22 XL	92	W	8.50	248	707	630	1389	340	50	E	B	73 2
	255/30R24 XL	97	W	9.00	260	764	730	1609	340	50	E	B	73 2
	295/30R26 XL	107	W	10.50	301	838	975	2149	340	50	E	B	73 2
	305/30R26 XL	109	V	11.00	313	844	1030	2271	340	50	E	B	73 2
35	265/35R22 XL	102	V	9.50	271	745	850	1874	340	50	E	B	73 2
	295/35R24 XL	110	V	10.50	301	816	1060	2337	340	50	E	B	73 2
	305/35R24 XL	112	V	11.00	313	824	1120	2469	340	50	E	B	73 2
40	245/40R20 XL	99	W	8.50	248	704	775	1709	340	50	E	B	73 2
	275/40R20 XL	106	V	9.50	278	728	950	2094	340	50	E	B	73 2
	265/40R22 XL	106	V	9.50	271	771	950	2094	340	50	E	B	73 2
	305/40R22 XL	114	V	11.00	313	803	1180	2601	340	50	E	B	73 2
45	275/45R20 XL	110	V	9.00	273	756	1060	2337	340	50	E	B	73 2
	285/45R22 XL	114	V	9.50	285	815	1180	2601	340	50	E	B	73 2
	305/45R22 XL	118	V	10.00	303	833	1320	2910	340	50	E	B	73 2
50	265/50R20 XL	111	V	8.50	277	774	1090	2403	340	50	E	B	73 2
	285/50R20 XL	116	V	9.00	297	794	1250	2756	340	50	E	B	73 2
55	275/55R20 XL	117	V	8.50	284	810	1285	2833	340	50	E	B	73 2
60	275/60R20	115	V	8.00	279	838	1215	2679	350	51	E	B	73 2

UTQG Treadwear 460 Traction A Temperature A

STRENGTH
POWER
DURABILITY

SURETREK
RY86

SURETREK H/T RY88

- The design of 4 directional grooves and intensive steel sheet specialises in both superior snowy and dry handling, increases safety and traction ability.
- Rectangular shoulder design updates grip and drive stability.
- Silencing technology is applied to offer low noise levels performance and a comfortable ride. Large pattern design in the shoulder increases braking, diversion and drainage performance.

Series	Size	Side Wall	LI	SS	Std.Rim	Section Width(mm)	Overall Diameter(mm)	Max. Load		Max. Pressure	
								kgs	lbs	kpa	psi
65	235/65R17	BSW	104	T	7.00	240	738	900	1984	250	36
	245/65R17	BSW	107	T	7.00	248	750	975	2149	250	36
70	215/70R16	OWL	100	H	6.50	221	708	800	1764	250	36
	225/70R16	OWL	103	T	6.50	228	722	875	1929	250	36
	235/70R16	OWL	106	T	7.00	240	736	950	2094	250	36
	245/70R16	OWL	107	T	7.00	248	750	1090	2403	250	36
	265/70R16	OWL	112	T	8.00	272	778	1120	2469	250	36
	265/70R17	OWL	115	T	8.00	272	804	1215	2679	250	36
	LT265/70R17 E	BSW	121	R	8.00	272	804	1450	3195	550	80
	LT285/70R17 D	BSW	121	S	8.50	292	832	1450	3195	450	65
75	235/75R15 XL	OWL	109	T	6.50	235	733	1030	2271	290	42
	265/75R16	OWL	116	T	7.50	267	804	1250	2756	250	36
	LT225/75R16 E	BSW	115	R	6.00	223	744	1215	2680	550	80
	LT245/75R16 E	BSW	120	R	7.00	248	774	1380	3042	550	80
	LT265/75R16 E	BSW	123	R	7.50	267	804	1550	3415	550	80
	LT245/75R17 E	BSW	121	R	7.00	248	800	1450	3195	550	80
80	LT235/80R17 E	BSW	120	R	6.50	235	808	1400	3085	550	80
85	LT235/85R16 E	BSW	120	R	6.50	235	806	1380	3042	550	80
	LT31X10.50R15 C	BSW	109	R	8.50	268	775	1030	2270	350	50

UTQG Treadwear 600 Traction A Temperature A

SURETREK H/T RY88

**STRENGTH
POWER
DURABILITY**

ROADTREK RY55



ROADTREK RY55

- Wide four ribs improve miles to tread life
- Zig-zag grooves offers enhanced traction on wet road
- Combination construction of polyester casing and steel belts provide outstanding durability

Series	Size	Side Wall	LI	SS	Std.Rim	Section Width(mm)	Overall Diameter(mm)	Max. Load		Max.Pressure	
								kgs	lbs	kpa	psi
60	215/60R16C	BSW	103/101	T	6.5	221	664	875	1929	375	54
65	205/65R16C	BSW	107/105	T	6	209	672	975	2149	475	69
	215/65R16C	BSW	109/107	R	6.5	221	686	1030	2271	475	69
	225/65R16C	BSW	112/110	R	6.5	228	698	1120	2469	475	69
	235/65R16C	BSW	115/113	R	7	240	712	1215	2679	475	69
70	195/70R15C	BSW	104/102	R	6	201	655	900	1984	450	65
	205/70R15C	BSW	106/104	R	6	209	669	950	2094	450	65
	215/70R15C	BSW	109/107	R	6.5	221	683	1030	2271	450	65
	225/70R15C	BSW	112/110	R	6.5	228	697	1120	2469	450	65
75	185/75R16C	BSW	104/102	R	5	184	684	900	1984	475	69
	195/75R16C	BSW	107/105	R	5.5	196	698	975	2149	475	69
	205/75R16C	BSW	110/108	R	5.5	203	714	1060	2337	475	69
	215/75R16C	BSW	113/111	R	6	216	728	1150	2535	475	69
80	185R14C	WSW	102/100	Q	5.5	188	650	850	1874	450	65
	195R14C	WSW	106/104	Q	5.5	198	666	950	2094	450	65
	205R14C	WSW	109/107	Q	6	208	686	1030	2271	450	65
	195R15C	WSW	106/104	R	5.5	196	693	950	2094	450	65
	205R16C	WSW	110/108	R	6	208	736	1060	2337	450	65

**STRENGTH
POWER
DURABILITY**