



AT738

- Application:drive wheel,long distance
- Suitable for highway and good road condition
- Mixed tread pattern,with good traction character
- Good anti-wearing character,long one-time mileage

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER $\pm 1.0\%$	SECTION WIDTH $\pm 4.0\%$
10.00R20	18	149/146	J	20.5	7.5	7.50V,8.0	3250	3000	930	1065	278
12R22.5	18	152/149	L	20	9.00	8.25	3550	3250	930	1085	300
13R22.5	18	154/151	K	20.5	9.75	9.00	3750	3450	830	1124	320
295/80R22.5	18	152/149	L	22	9.00	8.25	3550	3250	900	1044	298
315/80R22.5	20	156/153	K	22	9.00	9.75	4000	3650	900	1076	312



AT715

- Application:steer and trailer wheel,long distance use
- Suitable for highway and good road condition
- With good anti-side-skid character,low rolling resistance, low noise and excellent high speed driving character
- Adopt low-heating high anti-wearing formula, travel distance has been greatly increased

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER $\pm 1.0\%$	SECTION WIDTH $\pm 4.0\%$
385/65R22.5	18	158	K	16	11.75	12.25	4250		830	1072	389
385/65R22.5	20	160	K	16	11.75	12.25	4500		900	1072	389



AT706

- Application: steel wheel and trailer wheel, can also be used on drive wheel, long haul use
- Suitable for good road surface application
- With excellent anti-side-skid character and good drainage character, low rolling resistance, excellent high speed driving character
- Adopt low-heating high anti-wearing formula, travel distance has been greatly increased

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER $\pm 1.0\%$	SECTION WIDTH $\pm 4.0\%$
8.25R20	14	136/134	L	13	6.5	6.50T, 7.0, 7.00T	2240	2120	830	974	236
8.25R20	16	139/137	L	13	6.5	6.50T, 7.0, 7.00T	2430	2300	930	974	236
9.00R20	16	144/142	L	14	7.0	7.00T, 7.5	2800	2650	900	1019	259
10.00R20	16	146/143	L	15	7.5	7.50V, 8.0	3000	2725	830	1054	278
10.00R20	18	149/146	J	15	7.5	7.50V, 8.0	3250	3000	930	1054	278
11.00R20	16	150/147	K	16	8.0	8.00V, 8.5	3350	3075	830	1085	293
11.00R20	18	152/149	J	16	8.0	8.00V, 8.5	3550	3250	930	1085	293
9R22.5	12	133/131	M	13	6.75	6.00, 7.50	2060	1950	720	974	229
9R22.5	14	136/134	M	13	6.75	6.00, 7.50	2240	2120	830	974	229
10R22.5	16	144/142	M	14	7.50	6.75	2800	2650	900	1019	254
11R22.5	16	146/143	M	15	8.25	7.50	3000	2725	830	1054	279
12R22.5	16	150/147	M	16	9.00	8.25	3350	3075	830	1085	300
275/80R22.5	16	147/144	M	14	8.25	7.50	3075	2800	830	1012	276
295/80R22.5	16	150/147	M	17	9.00	8.25	3350	3075	830	1044	298
295/80R22.5	18	152/149	M	17	9.00	8.25	3550	3250	900	1044	298
315/80R22.5	18	154/151	M	19	9.00	9.75	3750	3450	830	1076	312
315/80R22.5	20	157/154	L	19	9.00	9.75	4125	3750	900	1076	312



AT719

- Application:all wheel on bus,steer wheel and trailer wheel on long distance truck
- Suitable for highway and good road condition
- With good drain and side-skidding resistance character
- With good anti-uneven wearing character

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER ±1.0%	SECTION WIDTH ±4.0%
11R22.5	16	146/143	M	15	8.25	7.50	3000	2725	830	1054	279
12R22.5	16	150/147	M	15.5	9.00	8.25	3350	3075	830	1085	300
12R22.5	18	152/149	M	15.5	9.00	8.25	3550	3250	930	1085	300
13R22.5	18	154/151	M	15.5	9.75	9.00	3750	3450	830	1124	320
295/80R22.5	16	150/147	M	15.5	9.00	8.25	3350	3075	830	1044	298
315/80R22.5	18	154/151	M	17	9.00	9.75	3750	3450	830	1076	312
315/80R22.5	20	157/154	L	17	9.00	9.75	4125	3750	900	1076	312
11.00R20	16	150/147	K	16	8.0	8.00V,8.5	3350	3075	830	1085	293
11.00R20	18	152/149	J	16	8.0	8.00V,8.5	3550	3250	930	1085	293



AT725

- Application: drive wheel,long haul use
- Suitable for highway and good road condition
- Mixed design tread pattern,with good traction character
- Good anti-wearing character,long one-time mileage

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER ±1.0%	SECTION WIDTH ±4.0%
295/80R22.5	16	150/147	M	18	9.00	8.25	3350	3075	830	1050	298
295/80R22.5	18	152/149	M	18	9.00	8.25	3550	3250	900	1050	298
315/80R22.5	18	154/151	M	19	9.00	9.75	3750	3450	830	1082	312
315/80R22.5	20	157/154	L	17	9	9.75	4125	3750	900	1082	312



AT701

- Application: all wheel,highway and expressway,medium and long distance
- Unique formula specially designed for this pattern,with excellent abrasion resistance
- Four vertical pattern groove design provide an excellent high speed driving character and good handling quality
- Unique design of the pattern bottom could effectively prevent groove cracking phenomenon due to clamp stones
- Transverse groove design can increase the effective grounding area,improve the anti-slippy character

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER ±1.0%	SECTION WIDTH ±4.0%
11R24.5	16	149/146	M	17	8.25	7.50	3250	3000	830	1104	279
295/75R22.5	16	146/143	M	16	9.00	8.25	3000	2725	830	1044	298



AT791

- Application: steer wheel,suitable for good road condition such as highway,expressway
- Super handling and anti-side-skid performance
- Special groove design could effectively prevent groove cracking phenomenon due to clamp stones,good self-cleaning performance
- Super anti-wear and low heat generating performance,suitable for high speed and long distance driving
- Low rolling resistance design could effectively reduce fuel consumption

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER ±1.0%	SECTION WIDTH ±4.0%
12R22.5	16	150/147	M	17	9.00	8.25	3350	3075	830	1085	300
12R22.5	18	152/149	M	17	9.00	8.25	3550	3250	930	1085	300
255/70R22.5	14	138/134	M	14	7.50	8.25	2360	2120	760	930	255
255/70R22.5	16	140/137	M	14	7.50	8.25	2500	2300	830	930	255
275/70R22.5	14	142/139	M	15	8.25	9.00	2650	2430	760	958	276
275/70R22.5	16	144/141	M	15	8.25	9.00	2800	2575	830	958	276
295/80R22.5	16	150/147	M	17	9.00	8.25	3350	3075	830	1044	298
295/80R22.5	18	152/149	M	17	9.00	8.25	3550	3250	900	1044	298
315/80R22.5	18	154/151	M	17	9.00	9.75	3750	3450	830	1076	312



AT707

- Application: installed on drive wheel for middle-and-long range transport
- Suitable for highway and good quality road
- Pattern with mixed design has powerful grip ability, excellent traction character
- Good high-speed and anti-puncture character
- Adopt low-heating high anti-wearing formula, travel distance has been greatly increased

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER ±1.0%	SECTION WIDTH ±4.0%
9.00R20	16	144/142	L	16	7.0	7.00T,7.5	2800	2650	900	1030	259
10.00R20	16	146/143	L	17	7.5	7.50V,8.0	3000	2725	830	1054	278
10.00R20	18	149/146	K	17	7.5	7.50V,8.0	3250	3000	930	1054	278
11.00R20	16	150/147	K	17	8.0	8.00V,8.5	3350	3075	830	1085	293
11.00R20	18	152/149	J	17	8.0	8.00V,8.5	3550	3250	930	1085	293
10R22.5	16	144/142	M	16	7.50	6.75	2800	2650	900	1019	254
11R22.5	16	146/143	M	17	8.25	7.50	3000	2725	830	1054	279
12R22.5	16	150/147	M	17	9.00	8.25	3350	3075	830	1085	300
275/80R22.5	16	147/144	M	16	8.25	7.50	3075	2800	830	1012	276
295/80R22.5	16	150/147	M	20	9.00	8.25	3350	3075	830	1050	298
295/80R22.5	18	152/149	M	20	9.00	8.25	3550	3250	900	1050	298
315/80R22.5	18	154/151	M	20	9.00	9.75	3750	3450	830	1082	312



AT732

- Application: all wheel, regional use
- Suitable for good road surface, such as classified road
- Mixed pattern design, with good traction character
- Good anti-wearing character, long one-time mileage

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER ±1.0%	SECTION WIDTH ±4.0%
12R22.5	16	150/147	M	17	8.25	9.00	3350	3075	830	1085	300
12R22.5	18	152/149	M	17	9.00	9.00	3550	3250	930	1085	300
13R22.5	18	154/151	L	17.5	9.00	9.75	3550	3450	830	1124	320



AT730

- Application: drive wheel, highway road surface, regional use
- With excellent tractive performance and brake performance for the pattern of thick blocks and crisscross horizontal pattern groove
- Low heat generating ,good anti-crack character, good abrasion resistance
- Tread minor groove design has improved the anti-slippery character and lower the uneven weariness on tread greatly

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER ±1.0%	SECTION WIDTH ±4.0%
11R22.5	14	144/142	M	20.5	8.25	7.50	2800	2650	720	1065	279
11R22.5	16	146/143	M	20.5	8.25	7.50	3000	2725	830	1065	279
10.00R20	16	146/143	K	18	7.5	7.50V,8.0	3000	2725	830	1065	278
10.00R20	18	149/146	J	18	7.5	7.50V,8.0	3250	3000	930	1065	278
11.00R20	16	150/147	K	18.5	8.0	8.00V,8.5	3350	3075	830	1096	293
11.00R20	18	152/149	J	18.5	8.0	8.00V,8.5	3550	3250	930	1096	293
12.00R20	18	154/151	K	19	8.5	8.50V,9.0	3750	3450	830	1136	315



AT710

- Application: installed on drive wheel or steering wheel
- Special pattern design, suitable for low speed ride on bad road condition, such as mining area
- With powerful grip ability and passing through character
- Good self-cleaning character, anti-wear character and anti-puncture character

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER ±1.0%	SECTION WIDTH ±4.0%
9.00R20	16	144/142	F	19	7.0	7.00T,7.5	2800	2650	900	1030	259
10.00R20	16	146/143	F	20.5	7.5	7.50V,8.0	3000	2725	830	1065	278
10.00R20	18	149/146	F	20.5	7.5	7.50V,8.0	3250	3000	930	1065	278
11.00R20	18	152/149	F	21	8.0	8.00V,8.5	3550	3250	930	1096	293
12.00R20	18	154/151	F	21.5	8.5	8.50V,9.0	3750	3450	830	1136	315



AT708

- Application:steer wheel,drive wheel and trailer wheel,on/off application
- Suitable for mixed road surface and relatively poor road surface
- With excellent crack and tear resistance character
- Adopt low heating high anti-wearing formula,travel distance has been greatly increased

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER $\pm 1.0\%$	SECTION WIDTH $\pm 4.0\%$
7.50R16	14	122/118	L	13	6.00G	5.50F,6.50H	1500	1320	770	805	215
8.25R16	16	128/124	K	14	6.50H	6.00G,6.50	1800	1600	770	855	235
8.25R20	16	139/137	L	15	6.5	6.50T,7.0,7.00T	2430	2300	930	974	236
9.00R20	16	144/142	K	15.5	7.0	7.00T,7.5	2800	2650	900	1019	259
10.00R20	16	146/143	K	17	7.5	7.50V,8.0	3000	2725	830	1054	278
10.00R20	18	149/146	J	17	7.5	7.50V,8.0	3250	3000	930	1054	278
11.00R20	16	150/147	K	17	8.0	8.00V,8.5	3350	3075	830	1085	293
11.00R20	18	152/149	K	17	8.0	8.00V,8.5	3550	3250	930	1085	293
12.00R20	18	154/151	K	17.5	8.5	8.50V,9.0	3750	3450	830	1125	315
12.00R20	20	156/153	J	17.5	8.5	8.50V,9.0	4000	3650	900	1125	315
12.00R24	18	158/155	K	17.5	8.5	8.50V,9.0	4250	3875	830	1226	315
12.00R24	20	160/157	K	17.5	8.5	8.50V,9.0	4500	4125	900	1226	315
11R24.5	16	149/146	M	17	8.25	7.50	3250	3000	830	1104	279
11R22.5	16	146/143	K	17	8.25	7.50	3000	2725	830	1054	279
12R22.5	16	150/147	L	17	9.00	8.25	3350	3075	830	1085	300
13R22.5	18	154/151	L	17.5	9.75	9.00	3750	3450	830	1124	320
315/80R22.5	18	154/151	L	17.5	9.00	9.75	3750	3450	830	1076	312



AT736

- Application:drive wheel
- Suitable for construction site
- Excellent traction performance and through performance
- With anti-breach and anti-puncture character

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER $\pm 1.0\%$	SECTION WIDTH $\pm 4.0\%$
8.25R16	16	128/124	K	16.5	6.50H	6.00G,6.50	1800	1600	770	865	235
8.25R20	16	139/137	K	16.5	6.5	6.50T,7.0,7.00T	2430	2300	930	986	236
10.00R20	16	146/143	K	19	7.5	7.50V,8.0	3000	2725	830	1065	278
10.00R20	18	149/146	K	19	7.5	7.50V,8.0	3250	3000	930	1065	278
11.00R20	18	152/149	J	19	8.0	8.00V,8.5	3550	3250	930	1096	293
12.00R20	18	154/151	K	20	8.5	8.50V,9.0	3450	3000	830	1136	315



AT712

- Application:steer wheel,drive wheel and trailer wheel
- Suitable for mixed road surface and relatively poor road surface
- With excellent crack and tear resistance character
- Adopt low-heating high anti-wearing formula,travel distance has been greatly increased

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER $\pm 1.0\%$	SECTION WIDTH $\pm 4.0\%$
10.00R20	18	149/146	J	17	7.5	7.50V,8.0	3250	3000	930	1054	278
11.00R20	16	150/147	K	17	8.0	8.00V,8.5	3350	3075	830	1085	293
11.00R20	18	152/149	J	17	8.0	8.00V,8.5	3550	3250	930	1085	293
12.00R20	18	154/151	K	17.5	8.5	8.50V,9.0	3750	3450	830	1125	315
12.00R24	18	158/155	K	17.5	8.5	8.50V,9.0	4250	3875	830	1226	315
12.00R24	20	160/157	K	17.5	8.5	8.50V,9.0	4500	4125	930	1226	315



AT727

- Application: drive wheel, highway and mixed road surface, regional use
- With excellent tractive performance and brake performance for the pattern of thick blocks and crisscross horizontal pattern groove
- Low heat generating, good anti-crack character, good abrasion resistance
- Tread minor groove design has improved the anti-slippery character and lower the uneven wear on tread greatly

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER $\pm 1.0\%$	SECTION WIDTH $\pm 4.0\%$
10.00R20	16	146/143	L	17.5	7.5	7.50V,8.0	3000	2725	830	1054	278
10.00R20	18	149/146	K	17.5	7.5	7.50V,8.0	3250	3000	930	1054	278
11.00R20	16	150/147	L	17.5	8.0	8.00V,8.5	3350	3075	830	1085	293
11.00R20	18	152/149	K	17.5	8.0	8.00V,8.5	3550	3250	930	1085	293
315/70R22.5	16	149/146	L	17	9.00	9.75	3250	3000	760	1014	312
13R22.5	18	154/151	L	17.5	9.75	9.00	3750	3450	830	1124	320



AT709

- Application: drive wheel
- Suitable for driving on roads like construction sites
- Good anti-crack character and good anti-puncture character
- Good traction character and passing through character
- Adopt low-heating high anti-wearing formula, travel distance has been greatly increased

SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	PATTERN DEPTH	STANDARD RIM	PERMITTED RIM	MAX LOAD (kg)		PRESSURE (kpa)	NEW TYRE INFLATION DIMENSION(MM)	
							S	D		OVERALL DIAMETER $\pm 1.0\%$	SECTION WIDTH $\pm 4.0\%$
8.25R16	16	128/124	K	14.5	6.50H	6.00G,6.50	1800	1600	770	855	235
9.00R20	16	144/142	K	16	7.0	7.00T,7.5	2800	2650	900	1019	259
10.00R20	16	146/143	L	17	7.5	7.50V,8.0	3000	2725	830	1054	278
10.00R20	18	149/146	J	17	7.5	7.50V,8.0	3250	3000	930	1054	278
11.00R20	16	150/147	K	17.5	8.0	8.00V,8.5	3350	3075	830	1085	293
11.00R20	18	152/149	J	17.5	8.0	8.00V,8.5	3550	3250	930	1085	293
12.00R20	18	154/151	K	18.5	8.5	8.50V,9.0	3750	3450	830	1125	315