

LH668

混合顺向花纹，优异的抓地性能，
防侧滑，变节距设计，低行驶噪音，
适合城乡各种路面使用

Mixed rib pattern; Good ground grasping capability;
Sideslip resistance; Pitch pattern designed; Low
noise, suitable for all kinds of the roads of the town.



特点 Benefits



轮位 Vehicle & Axes



规格 SIZE	轴 PIN	标准载荷 (kg/STD)	有无内胎 (TL/TT)	负荷指数 (LOAD INDEX)	速度级别 (SPEED RATING)	充气压力 (PSI/MPa/Bar)	最大负荷 (Max Loading) 单轴 SINGLE 双轴 DUAL	胎面宽 (mm)	外直径 (mm)	花纹深度 (mm)
8.25R20	14	6.5	TT	136/134	K	830	2240 2120	236	974	13.5
	16	6.5	TT	139/137	K	930	2430 2300	236	974	13.5
9.00R20	16	6.5	TT	144/142	L	900	2800 2650	258	1019	15.5
10.00R20	16	7.5	TT	146/143	L	830	3000 2725	278	1054	17
	18	7.5	TT	149/146	K	930	3250 3000	278	1054	17
	16	8.00	TT	150/147	L	830	3350 3075	293	1085	17
11.00R20	18	8.00	TT	152/149	K	930	3550 3250	293	1085	17
	18	8.5	TT	154/151	K	830	3750 3450	315	1125	17.5
12.00R20	20	8.5	TT	156/153	K	900	4000 3650	315	1125	17.5
	18	8.5	TT	158/155	K	830	4250 3875	315	1226	16
12.00R24	20	8.5	TT	160/157	K	900	4500 4125	315	1226	16

规格 SIZE	轴 PIN	标准载荷 (kg/STD)	有无内胎 (TL/TT)	负荷指数 (LOAD INDEX)	速度级别 (SPEED RATING)	充气压力 (PSI/MPa/Bar)	最大负荷 (Max Loading) 单轴 SINGLE 双轴 DUAL	胎面宽 (mm)	外直径 (mm)	花纹深度 (mm)
6.50R16LT	12	5.50F	TT	110/105	L	670	1060 925	185	750	12
7.00R16LT	12	5.50F	TT	115/110	L	670	1215 1060	200	775	12
	14	5.50F	TT	118/114	L	770	1320 1180	200	775	12
7.50R16LT	14	6.00G	TT	122/118	L	770	1500 1320	215	805	12
8.25R16LT	14	6.50H	TT	126/122	L	670	1700 1500	235	855	13
	16	6.50H	TT	128/124	L	770	1800 1600	235	855	13
11R22.5	14	8.25	TL	144/142	M	720	2800 2650	279	1054	15
	16	8.25	TL	146/143	L	830	3000 2750	279	1054	15
12R22.5	18	9.00	TL	152/149	L	930	3550 3250	300	1085	17.5
13R22.5	18	9.75	TL	154/151	L	830	3750 3450	320	1124	17.5
	20	9.75	TL	156/153	L	850	4000 3650	320	1124	17.5
315/80R22.5	18	9.00	TL	154/151	L	830	3750 3450	312	1076	17.5
	20	9.00	TL	156/153	L	850	4000 3650	312	1076	17.5



LH268

宽厚胎面花纹块，超深花纹设计，提供强劲动力，轮胎采用超强结构，具有优异的承载能力，高行驶寿命，耐磨、抗刺扎。适用于时速低于40公里的短途运输及要求耐切割、防掉块的铁矿、石料矿等较差路况。

Wide and thick blocks, extra deep tread depth, offer excellent traction.



LH599

在雪地，泥泞路面均具有较强的地面附着性能，优异的牵引，耐磨性能，行驶噪音低，具有较高的行驶里程。

Wide and thick blocks, extra deep tread depth, offer excellent traction; Designed with strong structure, good load capacity; Long service life, good anti-puncture attributes; Suitable to mine and moun and mountain roads.

特点 Benefits

轮位 Vehicle & Axles



规格 SIZE	轮位 PR	标准轮胎 STANDARD	有无内胎 R/T	负载指数 LOAD INDEX	速度级别 SPEED RATING	充气压力 PRESSURE PSI	最大负载 (kg) Max Load	标准负载 STANDARD	外肩径 OUTER DIA	花纹深度 TREAD	
8.25R16LT	14	6.50H	TT	126/122	L	670	1700	1500	235	855	16.5
	16	6.50H	TT	128/124	L	770	1800	1600	235	855	16.5
9.00R20	16	6.5	TT	144/142	L	900	2800	2650	258	1019	20
10.00R20	16	7.5	TT	146/143	L	830	3000	2725	278	1054	21
	18	7.5	TT	149/146	K	930	3250	3000	278	1054	21
11.00R20	18	8.0	TT	152/149	K	930	3550	3250	293	1094	22
12.00R20	20	8.5	TT	156/153	K	900	4000	3650	315	1122	23

特点 Benefits

轮位 Vehicle & Axles



规格 SIZE	位 PR	标准轮胎 STANDARD	有无内胎 R/T	负载指数 LOAD INDEX	速度级别 SPEED RATING	充气压力 PRESSURE PSI	最大负载 (kg) Max Load	标准负载 STANDARD	外肩径 OUTER DIA	花纹深度 TREAD	
11.00R20	16	8.0	TT	150/147	L	830	3350	3075	293	1085	20
	18	8.0	TT	152/149	K	930	3550	3250	293	1085	20
12.00R20	18	8.5	TT	154/151	K	830	3750	3450	315	1125	20
	20	8.5	TT	156/153	K	900	4000	3650	315	1125	20



LH999

宽厚胎面花纹块，超深花纹设计，提供强劲动力。
轮胎采用超强结构，具有优异的承载能力。
高行驶寿命，耐磨、抗刺扎。
适用于矿山、山地路面使用。

Wide and thick blocks, extra deep tread depth, offer excellent traction; Designed with strong structure, good load capacity; Long service life, good anti-puncture attributes; Suitable to mine and moun and mountain roads.



LH168

宽厚胎面花纹块，超深花纹设计，提供强劲动力。
轮胎采用超强结构，具有优异的承载能力高行驶寿命。
耐磨、抗刺扎，适用于矿山、山地路面使用。

Wide and thick blocks, extra deep tread depth, offer excellent traction; Designed with strong structure; Good load capacity; Long service life; Good anti-puncture attributes; Suitable to mine and moun and mountain roads.

特点 Benefits

轮位 Vehicle & Axles



规格 SIZE	尺寸 INCH	标准胎面 STANDARD TREAD	名义内径 NOMINAL RIM DIA.	使用负荷 LOAD RATING	速度级别 SPEED RATING	充气压力 PRESSURE PSI	最大负荷 Max Loading kg	滚动阻力 ROLLING RESISTANCE	胎面宽度 TREAD WIDTH (mm)	胎面深度 TREAD DEPTH (mm)	
10.00R20	16	7.5	TT	146/143	L	830	3000	2725	278	1054	19
	18	7.5	TT	149/146	K	930	3250	3000	278	1054	19
11.00R20	16	8.0	TT	150/147	L	830	3350	3075	293	1085	20
	18	8.0	TT	152/149	K	930	3550	3250	293	1085	20
12.00R20	18	8.5	TT	154/151	K	830	3750	3450	315	1125	20
	20	8.5	TT	156/153	K	900	4000	3650	315	1125	20
7.50R16LT	14	6.00G	TT	112/118	L	770	1500	1320	215	805	15.5
8.25R16LT	14	6.50H	TT	126/122	L	670	1700	1500	235	855	16.5
	16	6.50H	TT	128/124	L	770	1800	1600	235	855	16.5

特点 Benefits

轮位 Vehicle & Axles



规格 SIZE	尺寸 INCH	标准胎面 STANDARD TREAD	有无内胎	使用负荷 LOAD RATING	速度级别 SPEED RATING	充气压力 PRESSURE PSI	最大负荷 MAXIMUM LOAD		胎面宽度 TREAD WIDTH (mm)	胎面深度 TREAD DEPTH (mm)	滚动阻力
							标准胎面 STANDARD TREAD	花纹胎面 PATTERN TREAD			
10.00R20	16	7.5	TT	146/143	L	830	3000	2725	278	1054	17
	18	7.5	TT	149/146	K	930	3250	3000	278	1054	17
11.00R20	16	8.0	TT	150/147	L	830	3350	3075	293	1094	22
	18	8.0	TT	152/149	K	930	3550	3250	293	1094	22
12.00R20	18	8.5	TT	154/151	K	830	3750	3450	315	1122	23
	20	8.5	TT	156/153	K	900	4000	3650	315	1122	23



LH898

高性能混合花纹，半独立冠部花纹
一体化肩部花纹，高负荷能力
适用于各种复杂路面使用

High powered mixed pattern; High loading capacity;
Quasi-sovereign tread pattern; integrative shoulder
pattern; Suitable for all kinds of the roads.



LH288

宽厚胎面花纹块，超深花纹设计，
提供强劲动力，轮胎采用超强结构，
具有优异的承载能力高行驶寿命，
耐磨、抗刺扎。

Wide and thick blocks, extra deep tread depth, offer
excellent traction;
Designed with strong structure, good load capacity;
Long service life;
Good anti-puncture attributes;
Suitable to mine and moun and mountain roads.

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	层数 PR	标准胎面 STANDARD	有束内中 T/TT	负荷指数 LOAD INDEX	速度级别 SPEED GRADE	充气压力 PRESSURE PSI	最大负荷 Max Load 单轴 Single 双轴 Dual	断面宽 B.W.D	外直径 O.D	滚动直径 R.D
12.00R24	18	8.5	TT	158/155	K	830	4250 3875	315	1226	16
	20	8.5	TT	160/157	K	900	4500 4125	315	1226	16

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	层数 PR	标准胎面 STANDARD	有束内中 T/TT	负荷指数 LOAD INDEX	速度级别 SPEED GRADE	充气压力 PRESSURE PSI	最大负荷 Max Load 单轴 Single 双轴 Dual	断面宽 B.W.D	外直径 O.D	滚动直径 R.D
12.00R24	18	8.5	TT	158/155	K	830	4250 3875	315	1226	20
	20	8.5	TT	160/157	K	900	4500 4125	315	1226	20



LH399

高速、高载、超强的抗侧滑、
湿滑性能。适用于前轮位、全轮位

High speed;High loading capability;
Good sideslip and mud slip resistance;
Suitable for guiding and all use.



LH688

耐磨性好，载容量高，耐刺扎，
抓地性强既适用于较差路面，又
适用于较好路面

Good abrasion puncture resistance;Good loading
capability;Good grasping performance;Suitable for
rough road and high way.

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	轮位 PR	标准配置 STANDARD	有无内胎 R/L T/T	负载指数 LOAD INDEX	速度级别 SPEED RATING	充气压力 AIR PRESSURE PSI	最大负载 MAX.LOADING KG	轴间距 AXLE SPACING	外廓总 宽度 OUTLINE WIDTH	花纹深度 TREAD DEPTH	
11R22.5	14	8.25	TL	144/142	M	720	2800	2650	279	1054	15
	16	8.25	TL	146/143	L	830	3000	2750	279	1054	15
12R22.5	16	9.00	TL	150/147	M	830	3350	3075	300	1084	15
	18	9.00	TL	152/149	L	930	3550	3250	300	1084	15
295/80R22.5	16	9.00	TL	150/147	M	830	3350	3075	298	1044	15
	18	9.00	TL	152/149	L	850	3550	3250	298	1044	15
315/80R22.5	16	9.00	TL	151/148	M	760	3450	3150	312	1076	15
	18	9.00	TL	154/151	L	830	3750	3450	312	1076	15
	20	9.00	TL	156/153	L	850	4000	3650	312	1076	15

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	轮位 PR	标准配置 STANDARD	有无内胎 R/L T/T	负载指数 (LOAD INDEX)	速度级别 SPEED RATING	充气压力 AIR PRESSURE PSI	最大负荷 MAX.LOADING	轴距 AXLE SPACING	外廓总 宽度 OUTLINE WIDTH	花纹深度 TREAD DEPTH
12R22.5	16	9.00	TL	152/149	L	930	3550 3250	300	1085	23
315/80R22.5	18	9.00	TT	154/151	L	830	3750 3450	312	1076	23
	20	9.00	TT	156/153	L	850	4000 3650	312	1076	23



LH199

高速、重载、优异的牵引、制动、附着性能，
适用于驱动轮位。

High speed; High loading capability;
Good traction, braking and ground grasping
capability; Suitable for driving.



LH698

混合顺向花纹，优异的抓地性能，
防侧滑。变节距设计，低行驶噪音，
适用于城乡各种路面使用。

Mixed rib pattern; Good ground grasping capability;
Sidelip resistance; Pitch pattern designed;
Low noise; suitable for all kinds of the roads
of the town.

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	轮位 PR	标准载荷 (STANDARD LOADING) (kg)	有无内胎 (TYRE) (TYRE)	负荷指数 (LOAD INDEX)	速度级别 (SPEED RATING)	胎压 (INFLATION (kPa))	最大载重 (MaxLoading) (kg)	最大载重 (MaxLoading) (kg)	外载荷 (CUMULATIVE LOADING) (kg)	轮胎寿命 (km)	
12R22.5	16	9.00	TL	150/147	M	830	3350	3075	300	1085	17.5
295/80R22.5	18	9.00	TL	152/149	L	930	3550	3250	300	1085	17.5
	16	9.00	TL	150/147	M	830	3350	3075	298	1044	17.5
315/80R22.5	18	9.00	TL	152/149	L	900	3550	3250	298	1044	17.5
	18	9.00	TL	154/151	L	830	3750	3450	312	1076	18
	20	9.00	TL	156/153	L	850	4000	3650	312	1076	18

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	轮位 PR	标准载荷 STANDARD LOADING (kg)	有无内胎 TYRE TYRE	负荷指数 LOAD INDEX	速度级别 SPEED RATING	胎压 INFLATION (kPa)	最大载重 (MaxLoading)	前轴重 (F.W.AXLE)	外轴重 (O.AXLE)	轮胎深度 (TRA)
385/65R22.5	18	11.75	TL	158	M	830	4250	389	1072	15
	20	11.75	TL	160	L	830	4500	389	1072	15



LH188

适用于驱动轮：
适用于高速和优质路面的中短途运输。
具有出色的牵引性能和排水性能。
散热性能好，高速行驶更舒适。

Suitable for driving wheels in medium and short distance driving.
On common and higher level road.
Excellent traction and water evacuation performance.
Outstanding in heat dispersion and high speed driving.



LH299

适用于导向轮、驱动轮和拖车轴：
适用于高等级公路和高速公路。
具有更好的抗侧滑性能和抗爆胎性能。
独特的花纹设计，能有效减小路面不规则磨损，
优化散热性能良好，令驾驶更舒适，行驶更安全。

Suitable for all wheels on common and higher level highway.
Good performance of tearing resistance and abnormal wear of the shoulder in heat dispersion.
Safer and more comfortable driving experience.

特点 Benefits

轮位 Vehicle & Axles



规格 Spec	尺寸 Size	标准负荷 Standard load kg	轴重 Axle weight kg	轮胎宽度 Tyre width mm	速度等级 Speed grade	最大牵引力 Max pull (kg)		自重 Weight kg	滚动阻力 Rolling resistance		
						标准 Standard	满载 Full load				
12R22.5	16	9.00	TL	150/147	M	830	3350	3075	300	1085	20
	18	9.00	TL	152/149	L	930	3550	3250	300	1085	20

特点 Benefits

轮位 Vehicle & Axles



规格 Spec	尺寸 Size	标准负荷 Standard load	轴重 Axle weight	轮胎宽度 Tyre width	速度等级 Speed grade	最大牵引力 Max pull		牵引力 Pulling force	自重 Weight	滚动阻力 Rolling resistance	
						标准 100% Standard	选配 100% Option				
12R22.5	16	9.00	TL	150/147	M	830	3350	3075	300	1085	17.5
	18	9.00	TL	152/149	L	930	3550	3250	300	1085	17.5



LH598

高速、高载、超强的抗侧滑、
湿滑性能，适用于前轮位、全轮位

High speed/High loading capability;
Good sideslip and mud slip resistance;
Suitable for guiding and all use.



SFC57

混合顺向花纹，优异的抓地性能，
防侧滑，变节距设计，低行驶噪音，
适合城乡各种路面使用

Mixed rib pattern: Good ground grasping capability;
Sideslip resistance; Pitch pattern designed Low
noise, suitable for all kinds of the roads of the town.

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	胎宽 PR	标准轮距 STD GAUGE	前轴轮距 FLY TT	后轴轮距 LOAD RETR	速度等级 SPEED RATING	充气压力 AIR PRESSURE	最大负荷 MAX. LOADING 载重 CARRYING	新断面 NEW R&R	外直径 OUTSIDE DIA.	花纹深度 TREAD
12.00R20	18	8.5	TT	154/151	K	830	3750 3450	315	1125	22
	20	8.5	TT	156/153	K	900	4000 3650	315	1125	22
295/80R22.5	16	9.00	TL	150/147	M	830	3350 3075	298	1044	22
	18	9.00	TL	152/149	L	850	3550 3250	298	1044	22
13R22.5	18	9.75	TL	154/151	L	830	3750 3450	320	1124	22
	20	9.75	TL	156/153	L	850	4000 3650	320	1124	22

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	胎宽 PR	标准轮距 STANDARD	前轴轮距 FLY TT	后轴轮距 LOAD RETR	速度等级 SPEED RATING	充气压力 AIR PRESSURE	最大负荷 MAX. LOADING 载重 CARRYING	新断面 NEW R&R	外直径 OUTSIDE DIA.	花纹深度 TREAD
285/75R24.5	14	8.25	TL	144/141	M	760	2800 2575	283	1050	14
	16	8.25	TL	147/144	M	830	3075 2800	283	1050	14
11R24.5	14	8.25	TL	146/143	M	720	3000 2725	279	1104	14
	16	8.25	TL	149/146	M	830	3250 3000	279	1104	14
11R22.5	14	8.25	TL	144/142	M	720	2800 2650	279	1054	14
	16	8.25	TL	146/143	M	830	3000 2725	279	1054	14
295/75R22.5	14	9.00	TL	144/141	M	760	2800 2575	298	1014	14
	16	9.00	TL	146/143	M	830	3000 2725	298	1014	14



SFC76

Wheel position: For steer axle or trailers. Application: For highway and improved road surface. Characters: Having good anti-sideslip and anti-abnormal wear resistance performance and low rolling resistance performance. Also such a pattern has low heating-making and superior high-speed performance.



SFC59

耐磨性好, 载重量高, 耐刺扎, 抓着力强既适用于较差路面, 又适用于较好路面

Good abrasion puncture resistance; Good loading capability; Good grasping performance; Suitable for rough road and high way.

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	尺寸 R&R	标准花纹 STANDARD PATTERN	有无内胎 TYRE	负荷指数 LOAD INDEX	速度级别 SPEED RATING	充气压力 INFLATION PSI/KPa	最大负载 MAX. LOADING 重量 (kg/LB)	断面宽 WIDTH	外直径 ODMM	花纹深度 TREAD DEPTH
285/75R24.5	14	8.25	TL	144/141	M	760	2800 2575	283	1050	14
	16	8.25	TL	147/144	M	830	3075 2800	283	1050	14
11R24.5	14	8.25	TL	146/143	M	720	3000 2725	279	1104	14
	16	8.25	TL	149/146	M	830	3250 3000	279	1104	14
11R22.5	14	8.25	TL	144/142	M	720	2800 2650	279	1054	14
	16	8.25	TL	146/143	M	830	3000 2725	279	1054	14
295/75R22.5	14	9.00	TL	144/141	M	760	2800 2575	298	1014	14
	16	9.00	TL	146/143	M	830	3000 2725	298	1014	14
315/80R22.5	16	9.00	TL	151/148	M	760	3450 3150	312	1076	15
	18	9.00	TL	154/151	L	830	3750 3450	312	1076	15
	20	9.00	TL	156/153	L	850	4000 3650	312	1076	15

特点 Benefits



轮位 Vehicle & Axles



规格 SIZE	尺寸 R&R	标准花纹 STANDARD PATTERN	有无内胎 TYRE	负荷指数 LOAD INDEX	速度级别 SPEED RATING	充气压力 INFLATION PSI/KPa	最大负载 MAX. LOADING 重量 (kg/LB)	断面宽 WIDTH	外直径 ODMM	花纹深度 TREAD DEPTH
285/75R24.5	14	8.25	TL	144/141	M	760	2800 2575	283	1050	20
	16	8.25	TL	147/144	M	830	3075 2800	283	1050	20
11R24.5	14	8.25	TL	146/143	M	720	3000 2725	279	1104	20
	16	8.25	TL	149/146	M	830	3250 3000	279	1104	20
11R22.5	14	8.25	TL	144/142	M	720	2800 2650	279	1054	20
	16	8.25	TL	146/143	M	830	3000 2725	279	1054	20
295/75R22.5	14	9.00	TL	144/141	M	760	2800 2575	298	1014	20
	16	9.00	TL	146/143	M	830	3000 2725	298	1014	20



SFC07 NEW

混合斜向花纹，优异的抓地性能。
防侧滑，宽节距设计，低行驶噪音。
适合城乡各种路面使用。

Mixed rib pattern.Good ground grasping capability.
Sideslip resistance.Pitch pattern designed.Low
noise,suitable for all kinds of the roads of the town.



SFC02 NEW

混合斜向花纹，优异的抓地性能。
防侧滑，宽节距设计，低行驶噪音。
适合城乡各种路面使用。

Mixed rib pattern.Good ground grasping capability.
Sideslip resistance.Pitch pattern designed.Low
noise,suitable for all kinds of the roads of the town.

特点 Benefits

适用 Vehicle & Axes



规格 Spec	尺寸 Size	速度 最高 Speed max	花纹 Pattern	适用 轴数 适用 轴数 Applicable axles	适用 载重 适用 载重 Applicable load	适用 车速 适用 车速 Applicable speed	适用 载重 适用 载重 Applicable load	适用 车速 适用 车速 Applicable speed	适用 载重 适用 载重 Applicable load	适用 车速 适用 车速 Applicable speed
SFC070215	15	11.75	TL	156	M	830	4200	300	1372	15
	20	15.75	TL	160	L	800	4500	300	1372	15

特点 Benefits

适用 Vehicle & Axes



规格 Spec	尺寸 Size	速度 最高 Speed max	花纹 Pattern	适用 轴数 适用 轴数 Applicable axles	适用 载重 适用 载重 Applicable load	适用 车速 适用 车速 Applicable speed	适用 载重 适用 载重 Applicable load	适用 车速 适用 车速 Applicable speed	适用 载重 适用 载重 Applicable load	适用 车速 适用 车速 Applicable speed	
SFC02020	16	8.00	TL	150/147	L	830	2200	3075	293	1085	16
	16	8.00	TL	152/149	K	830	3000	3250	293	1085	16

★ NEW PLAN WILL OPEN



SFC 70

The all-position radial designed for highway and regional service with superb performance and handling.

★HIGHWAY
★REGIONAL



★ NEW PLAN WILL OPEN



SFC 77

The drive tire optimized for exceptional traction and wear in mixed and on/off road service.

★ON/OFF
★Mining
★SNOW



特点 Benefits



轮位 Vehicle & Axles

○BEST ○REF



规格 SIZE	位 PR	标准载荷 STANDARD LOAD	有无内胎 TL/TT	负荷指数 LOAD INDEX	速度级别 SPEED RATING	胎压 INFLATION PSI	最大载重 Max Loading 单胎 Single Axle	最大载重 Max Loading 双胎 Dual Axle	断面宽 WIDTH	外直径 OUTSIDE DIAMETER	轮距间距 HUB SPACING
215/75R17.5	12	6.00	TL	126/124	M	3750	1700	1600	209	775	12.6
225/75R17.5	12	6.75	TL	129/127	M	4080	1850	1750	228	790	12.6
235/75R17.5	14	6.75	TL	125/123	M	4080	1850	1750	228	790	13.6
225/70R19.5	12	6.75	TL	125/123	L	3640	1650	1550	225	816	12.6
245/70R19.5	14	7.50	TL	136/134	M	4940	2240	2120	248	843	13.5

特点 Benefits



轮位 Vehicle & Axles

○BEST ○REF



胎 宽 SIZE	位 数 PR	标准载荷 STANDARD LOAD	有无内胎 TL/TT	负荷指数 LOAD INDEX	速度级别 SPEED RATING	胎压 INFLATION PSI	最大载重 Max Loading	断面宽 WIDTH	外直径 OUTSIDE DIAMETER	轮距间距 HUB SPACING	
11R22.5	14	8.25	TL	144/142	M	720	2800	2650	279	1054	14
	16	8.25	TL	146/143	M	830	3000	2725	279	1054	14
	14	8.25	TL	146/143	M	720	3000	2725	279	1104	14
	16	8.25	TL	149/146	M	830	3250	3000	279	1104	14
295/80R22.5	16	9.00	TL	150/146	K	830	3350	3000	298	1044	18
	18	9.00	TL	152/148	J	850	3550	3150	298	1044	18
315/80R22.5	18	9.00	TL	154/151	K	830	3750	3450	312	1076	18
	20	9.00	TL	156/153	J	850	4000	3650	312	1076	18

★ NEW PLAN WILL OPEN



SFC 87

Suitable for drive axle for mixed transport.

- ★ OFF ROAD
- ★ MIXED ROAD
- ★ MINING

FEATURES

- ★ Special rubber compound designed for varied applications.
- ★ Reinforced crown ply to improve resistance against oxidation.
- ★ Broad, directional block tread.

BENEFITS

- ★ Good mileage potential.
- ★ Excellent resistance to damage and punctures on/off road.
- ★ Good on/off road grip.

特点 Benefits

轮位 Vehicle & Axles



○ BEST ○ REF



规格 SIZE	层级 PR	标准轮辋 STANDARD RIM	有无内胎 TL / TT	负荷指数 LOAD INDEX	速度级别 SPEED RATING	充气压力 PRESSURE (KPA)	最大负荷 MAX.LOAD(kg)		断面宽 S.W.(MM)	外直径 O.D.(MM)	花纹深度 (MM)
							单胎 SINGLE	双胎 DUAL			
295/80R22.5	16	9.00	TL	150/147	M	830	3350	3075	298	1044	20
	18	9.00	TL	152/149	L	850	3550	3250	298	1044	20
315/80R22.5	16	9.00	TL	151/148	M	760	3450	3150	312	1076	20
	18	9.00	TL	154/151	L	830	3750	3450	312	1076	20
	20	9.00	TL	156/153	L	850	4000	3650	312	1076	20
13R22.5	18	9.75	TL	154/151	L	830	3750	3450	320	1124	20
	20	9.75	TL	156/153	L	850	4000	3650	320	1124	20