

GR612 suitable for Long Haul road
GR622 suitable for Long Haul road



Economy



Good handling



Comfort



TRUCK & BUS RADIAL TIRES

GR612 BEST



Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
11R22.5	14.00	1048	8.25	14	G	144/142	M	2800/2650	6175/5840	720	105
11R22.5	14.00	1048	8.25	16	H	146/143	M	3000/2725	6610/6005	830	120
11R24.5	14.00	1098	8.25	14	G	146/143	M	3000/2725	6610/6005	720	105
11R24.5	14.00	1098	8.25	16	H	149/146	M	3250/3000	7160/6610	830	120
285/75R24.5	14.00	1049	8.25	14	G	144/141	M	2800/2575	6175/5675	760	110
285/75R24.5	14.00	1049	8.25	16	H	146/143	M	3000/2725	6610/6005	830	120
295/75R22.5	14.00	1011	9.00	14	G	144/141	M	2800/2575	6175/5675	760	110
295/75R22.5	14.00	1011	9.00	16	H	146/143	M	3000/2725	6610/6005	830	120
215/75R17.5	12.50	768	6.00	16	H	126/124	M	1700/1600	3750/3530	700	100
215/75R17.5	12.50	768	6.00	18	J	135/133	J	2180/2060	4805/4540	860	125
235/75R17.5	12.50	793	6.75	16	H	132/130	M	2000/1900	4409/4190	775	115
235/75R17.5	12.50	793	6.75	18	J	143/141	J	2725/2575	6005/5675	900	130
225/70R19.5	12.50	814	6.75	14	G	128/126	M	1800/1700	3970/3750	760	110
245/70R19.5	12.50	841	7.50	16	H	136/134	M	2240/2120	4940/4680	825	120
265/70R19.5	12.50	869	7.50	16	H	140/138	M	2500/2360	5510/5200	775	115
255/70R22.5	14.00	926	7.50	16	H	140/137	m	2500/2300	5510/5070	800	116
275/70R22.5	14.00	952	8.25	18	H	148/145	M	3150/2900	6945/6395	850	125
275/70R22.5	14.00	952	8.25	16	H	144/141	M	2800/2575	6175/5675	760	110

GR622 BEST



Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
11R22.5	21.00	1062	8.25	14	G	144/142	M	2800/2650	6175/5840	720	105
11R22.5	21.00	1062	8.25	16	H	146/143	M	3000/2725	6610/6005	830	120
11R24.5	21.00	1112	8.25	14	G	146/143	M	3000/2725	6610/6005	720	105
11R24.5	21.00	1112	8.25	16	H	149/146	M	3250/3000	7160/6610	830	120
285/75R24.5	21.00	1063	8.25	14	G	144/141	M	2800/2575	6175/5675	760	110
285/75R24.5	21.00	1063	8.25	16	H	146/143	M	3000/2725	6610/6005	830	120
295/75R22.5	21.00	1025	9.00	14	G	144/141	M	2800/2575	6175/5675	760	110
295/75R22.5	21.00	1025	9.00	16	H	146/143	M	3000/2725	6610/6005	830	120

GR612 MAIN TRAIT

- Fuel efficient with lower rolling resistance.
- Steer response.
- Resistance to shoulder edge wear.
- Wet handling.
- Strong wear resistant.
- Stone reject character design.

GR622 MAIN TRAIT

- Fuel efficient with lower rolling resistance.
- Excellent traction and wet weather handling.
- Optimized tread design and tread depth for long life.



GR636 suitable for Long Haul road
GR662 suitable for Regional road



Economy



Good handling



Comfort



TRUCK & BUS RADIAL TIRES

GR636



BEST



Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
11R22.5	11.00	1042	8.25	14	G	144/142	M	2800/2650	6175/5840	720	105
11R22.5	11.00	1042	8.25	16	H	146/143	M	3000/2725	6610/6005	830	120
11R24.5	11.00	1092	8.25	14	G	146/143	M	3000/2725	6610/6005	720	105
11R24.5	11.00	1092	8.25	16	H	149/146	M	3250/3000	7160/6610	830	120
285/75R24.5	11.00	1043	8.25	14	G	144/141	M	2800/2575	6175/5675	760	110
285/75R24.5	11.00	1043	8.25	16	H	146/143	M	3000/2725	6610/6005	830	120
295/75R22.5	11.00	1005	9.00	14	G	144/141	M	2800/2575	6175/5675	760	110
295/75R22.5	11.00	1005	9.00	16	H	146/143	M	3000/2725	6610/6005	830	120

GR662



BEST



Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
12R22.5	16.50	1074	9.00	18	J	152/149	M	3550/3250	7830/7160	930	135
12R22.5	16.00	1073	9.00	18	J	152/149	M	3550/3250	7830/7160	930	135
295/60R22.5	14.50	915	9.00	18	J	150/147	L	3350/3075	7385/6780	900	130
315/60R22.5	14.50	940	9.75	18	J	152/148	L	3550/3150	7825/6945	900	130
275/80R22.5	14.00	1012	8.25	16	H	149/146	M	3250/3000	7160/6610	850	125
295/80R22.5	15.00	1043	9.00	18	J	152/149	M	3550/3250	7830/7160	900	130
315/70R22.5	15.00	1012	9.00	18	J	152/148	M	3550/3150	7825/6945	830	120
315/80R22.5	16.00	1079	9.00	18	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	16.00	1079	9.00	20	L	156/150	M	4000/3350	8820/7385	850	125

GR636 MAIN TRAIT

- Fuel efficient with lower rolling resistance.
- Wide tread for long life.
- More suitable design for long distance and standard loading condition.
- Design for trailer position only.

GR662 MAIN TRAIT

- High way and long distance use.
- Fuel efficient with lower rolling resistance steer tyre.
- Excellent heat resistance performance .
- Low noisy.



01

GR636

02

GR662



GR678 suitable for Regional road
GR666 suitable for Regional road



Economy



Good handling



Comfort



TRUCK & BUS RADIAL TIRES

GR678 BEST



Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
12R22.5	20.00	1081	9.00	18	J	152/149	M	3550/3250	7830/7160	930	135
275/80R22.5	19.00	1021	8.25	16	H	149/146	M	3250/3000	7160/6610	850	125
295/80R22.5	20.00	1053	9.00	18	J	152/149	M	3550/3250	7830/7160	900	130
315/70R22.5	20.00	1022	9.00	18	J	152/148	M	3550/3150	7825/6945	830	120
315/80R22.5	20.00	1087	9.00	18	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	20.00	1087	9.00	20	L	156/150	M	4000/3350	8820/7385	850	125
215/75R17.5	15.00	773	6.00	16	H	126/124	M	1700/1600	3750/3530	700	100
215/75R17.5	15.00	773	6.00	18	J	135/133	J	2180/2060	4805/4540	860	125
235/75R17.5	15.00	798	6.75	16	H	132/130	M	2000/1900	4409/4190	775	115
235/75R17.5	15.00	798	6.75	18	J	143/141	J	2725/2575	6005/5675	900	130
225/70R19.5	15.00	819	6.75	14	G	128/126	M	1800/1700	3970/3750	760	110
245/70R19.5	15.00	846	7.50	16	H	136/134	M	2240/2120	4940/4680	825	120
265/70R19.5	15.00	874	7.50	16	H	140/138	M	2500/2360	5510/5200	775	115

GR666 BEST



Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
385/65R22.5	15.00	1066	11.75	20	L	160	K	4500	9920	900	130

GR678 MAIN TRAIT

- Fuel efficient drive tyre.
- No compromise on durability, irregular wear resistance and wet performance.
- Excellent traction and wet weather handling.
- High mileage in low severity operations.

GR666 MAIN TRAIT

- Fuel efficient with lower rolling resistance.
- High way use for trailer.
- No compromise on durability, irregular wear resistance and wet performance.
- Ride comfort& easy handling.



01 **GR678**

02 **GR666**



GR881 suitable for Regional, ON & OFF road
GR679 suitable for Regional, ON & OFF road



Economy



Good handling



Comfort



TRUCK & BUS RADIAL TIRES

GR881



BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
11R22.5	15.00	1050	8.25	16	H	146/143	M	3000/2725	6610/6005	830	120
11R22.5	15.00	1050	8.25	18	J	148/145	M	3150/2900	6945/6395	850	125
11R24.5	15.00	1098	8.25	14	G	146/143	M	3000/2725	6610/6005	720	105
11R24.5	15.00	1098	8.25	16	H	149/146	M	3250/3000	7160/6610	830	120
12R22.5	16.00	1073	9.00	18	J	152/149	M	3550/3250	7830/7160	930	135
6.50R16LT	9.50	749	5.50F	12	F	110/105	M	1060/925	2335/2040	670	100
7.00R16LT	10.50	775	5.50F	14	G	118/114	M	1320/1180	2910/2600	770	110
7.50R16LT	13.00	803	6.00G	14	G	122/118	L	1500/1320	3305/2910	770	110
8.25R16LT	13.00	852	6.50H	16	H	128/124	L	1800/1600	3975/3525	770	110
9.00R20	15.50	1020	7.00	16	H	144/142	L	2800/2650	6170/5840	900	130
10.00R20	16.50	1051	7.50	18	J	149/146	L	3250/3000	7160/6610	930	135
11.00R20	17.00	1085	8.00	18	J	152/149	L	3550/3250	7830/7160	930	135
12.00R20	16.50	1121	8.50	20	L	156/153	L	4000/3650	8820/8050	900	130
12.00R20	15.50	1115	8.50	20	L	156/153	L	4000/3650	8820/8050	900	130
12.00R24	17.50	1218	8.50	20	L	160/157	K	4500/4125	9920/9090	900	130
13R22.5	17.50	1117	9.75	18	J	156/150	L	4000/3350	8820/7385	875	126
315/80R22.5	16.00	1079	9.00	18	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	16.00	1079	9.00	20	L	156/150	M	4000/3350	8820/7385	850	125

GR679



BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
13R22.5	17.00	1116	9.75	18	J	156/150	L	4000/3350	8820/7385	875	126
315/80R22.5	20.00	1085	9.00	18	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	20.00	1085	9.00	20	L	156/150	M	4000/3350	8820/7385	850	125

GR881 MAIN TRAIT

- Classic pattern for all position under different road condition.
- Unique belt construction and tread heat resistance compound combining for strong traction and long life.
- Outstanding high-speed performance.
- S groove design for eliminate pattern damage and wet handling.

GR679 MAIN TRAIT

- Strong traction for drive.
- High resistance to irregular wears.
- Good wet handling.
- High mileage in low severity operations.



GR888 suitable for Regional road
GR665 suitable for Regional road



Economy



Good handling



Comfort



TRUCK & BUS RADIAL TIRES

GR888 BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
315/80R22.5	21.00	1087	9.00	18	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	21.00	1087	9.00	20	L	156/150	M	4000/3350	8820/7385	850	125

GR665 BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
12R22.5	21.50	1090	9.00	18	J	152/149	M	3550/3250	7830/7160	930	135

GR888 MAIN TRAIT

- Contact plus Design.
- Contact area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.

GR665 MAIN TRAIT

- Contour optimization design, ensure the tread of each block of uniform stress, prevent irregular wear.
- Special concave rill design, improve the tire heat dissipating performance and wetland grasping performance.
- Use low heat tread base rubber of tread decreased heat, which has excellent durability.
- Deepen semi open pattern design, shoulder design provides a good driving performance, suitable for driving wheel use.



01 **GR888**

02 **GR665**



GR982 suitable for Regional road
GR898 suitable for Regional road



Economy



Good handling



Comfort



TRUCK & BUS RADIAL TIRES

GR982 BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
12.00R24	14.50	1214	8.50	20	L	160/157	K	4500/4125	9920/9090	900	130

GR898 BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
12.00R24	15.50	1216	8.50	20	L	160/157	K	4500/4125	9920/9090	900	130

GR982 MAIN TRAIT

- The special pattern design keeping the best performance of stone shying.
- Optimized body design can keep sure the even landing, to avoid asymmetric wear.
- The basic rubber using low heat compound, to prolong the tire mileage.
- The small zigzag design on the tread providing more gripping power.

GR898 MAIN TRAIT

- Wide and deep horizontal pattern and shallow partition pattern provides strong traction, excellent gripping ability in dry and wet road condition.
- Mixed tread pattern especially designed for driving shaft. Deep pattern provides better mileage.
- Unique tread belt structure, tire crown/wing compound with high wear resistance and low heat generation.
- Optimized and reinforced tire bead design is suitable for middle or short distance heavy transportation on rough road.



01 **GR982**

02 **GR898**



GR661 suitable for Regional, ON & OFF road
GR663 suitable for Regional, ON & OFF road



Economy



Good handling



Comfort



TRUCK & BUS RADIAL TIRES

GR661



BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
12R22.5	18.00	1077	9.00	18	J	152/149	M	3550/3250	7830/7160	930	135
13R22.5	20.00	1124	9.75	18	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	18.00	1083	9.00	18	J	154/151	M	3750/3450	8270/7610	830	120
315/80R22.5	18.00	1083	9.00	20	L	156/150	M	4000/3350	8820/7385	850	125

GR663



BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
12R22.5	19.00	1079	9.00	18	J	152/149	M	3550/3250	7830/7160	930	135

GR661 MAIN TRAIT

- Deep tread for extra-long life.
- Good wet traction and driving stability in high speed.
- High resistance to cutting and abrasion.
- Low noisy.

GR663 MAIN TRAIT

- Designed for drive axle on highway and paved road.
- Excellent traction and wet weather handling.
- Strong construction offers high speed and load carrying durability.
- Deep tread groove give longest tyre life and high resistance to irregular wear.



01

GR661

02

GR663



GR882 suitable for Regional, ON & OFF road
GR883 suitable for Regional, ON & OFF road



Economy



Good handling



Comfort



TRUCK & BUS RADIAL TIRES

GR882 BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
12.00R24	20.00	1223	8.50	20	L	160/157	K	4500/4125	9920/9090	900	130
325/95R24	20.00	1223	9.00	20	L	160/157	K	4500/4125	9920/9090	900	130
325/95R24	20.00	1223	9.00	22	M	162/160	K	4750/4500	10470/9920	930	135
7.50R16LT	15.50	808	6.00G	14	G	122/118	L	1500/1320	3305/2910	770	110
8.25R16LT	16.00	858	6.50H	16	H	128/124	L	1800/1600	3975/3525	770	110
10.00R20	18.00	1054	7.50	18	J	149/146	L	3250/3000	7160/6610	930	135
11.00R20	18.00	1089	8.00	18	J	152/149	L	3550/3250	7830/7160	930	135
12.00R20	19.50	1125	8.50	20	L	156/153	L	4000/3650	8820/8050	900	130

GR883 BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
11.00R20	16.50	1084	8.00	18	J	152/149	L	3550/3250	7830/7160	930	135
12.00R20	18.00	1124	8.50	20	L	156/153	L	4000/3650	8820/8050	900	130

GR882 MAIN TRAIT

- High traction and heat resistance design.
- High cut-chip resistance.
- Strong construction for heavy load under bad road condition.
- Fuel efficient with long life.
- Strong drive power.

GR883 MAIN TRAIT

- Deep tread for extra-long life.
- Good wet traction and driving stability in high speed.
- High resistance to cutting and abrasion.
- Low noisy.



01 GR882

02 GR883

GR885 suitable for Mining road
GR886 suitable for Mining road



Economy



Good handling



TRUCK & BUS RADIAL TIRES


GR885



BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
11.00R20	23.00	1097	8.00	18	J	152/149	E	3550/3250	7830/7160	930	135
12.00R20	24.00	1131	8.50	20	L	156/153	E	4000/3650	8820/8050	900	130

GR886



BEST

Size	T.D.	O.D.	RIM	PR	L.R.	LI	SS	LI(KG)	LI(lbs)	Pressure (kPa)	Pressure (psi)
11.00R20	24.50	1100	8.00	18	J	152/149	E	3550/3250	7830/7160	930	135
12.00R20	25.50	1134	8.50	20	L	156/153	E	4000/3650	8820/8050	900	130

GR885 MAIN TRAIT

- Designed for drive axle use on mining and paved roads.
- Strong construction offers high load, carrying durability.
- Original block-pattern and deep tread groove give longest tyre life and high resistance to irregular wears. High traction to carry heavy load and for longer tyre life.
- Good self-cleaning.

GR886 MAIN TRAIT

- Designed for drive axle use on mining and paved roads.
- Strong construction offers high load, carrying durability.
- Original block-pattern and deep tread groove give longest tyre life and high resistance to irregular wears. High traction to carry heavy load and for longer tyre life.
- Good self-cleaning.



01 GR885

02 GR886