



101

Excellent tear resistance and load capacity.
Low rolling resistance & noise erosion, excellent guiding stability.
Excellent fuel efficiency.



102

Strong traction and braking power.
Enhanced the ability of unit eccentric wear.
Five deep grooves ,multi blocks&tiny serfs.



103

TMS technology and special compound for smooth tread wear.
Special pattern design provides good anti-eccentric wear.
Block tread.



106

Excellent traction and draining performance.
More original mileages.



107

High wear resistance, low heat generation.
Excellent traction and draining performance.
Super driving and anti-wet ability.



Heavy duty radial truck tire

www.roogootire.com

ROOGOO



109

Low heat generating.
Excellent high speed driving character.
Good handling quality.



201

Excellent load capacity.
Straight shallow grooves offers an excellent drive, straight ride and anti-sidewall scuffing performance.



202

Strong traction and braking power.
Enhanced the ability of anti eccentric wear.
Excellent grip.



203

Super abrasion resistance, high heat dissipation performance
Good handling and traction with higher original mileage.
Excellent fuel efficiency.



205

Improved tread design, high wear resistance and eccentric wear resistance.
Low rolling resistance ,save fuel consumption.



Tire Specifications

Pattern	Size	PR	Standard rim	Load index	Speed rating	Overall diameter	Section width	Max Load (kg)		Pressure
								Single	Dual	kpa
101	11R22.5	16	8.25	146/143	M	1050	279	3000	2725	830
	12R22.5	18	9.00	152/149	M	1084	300	3550	3250	930
	315/80R22.5	20	9.00	157/153	L	1076	312	4125	3650	870
	295/80R22.5	18	9.00	152/149	M	1044	298	3550	3250	900
102	315/80R22.5	20	9.00	157/153	L	1076	312	4125	3650	870
103	11R22.5	16	8.25	146/143	M	1050	279	3000	2725	830
	12R22.5	18	9.00	152/149	M	1084	300	3550	3250	930
	295/80R22.5	18	9.00	152/149	M	1044	298	3550	3250	900
105	12R22.5	18	9.00	152/149	M	1084	300	3550	3250	930
106	385/65R22.5	20	11.75	160	K	1072	389	4500	4500	900
107	12R22.5	18	9.00	152/149	M	1084	300	3550	3250	930
109	315/80R22.5	20	9.00	157/153	L	1076	312	4125	3650	870
201	315/70R22.5	20	9.00	157/153	L	1076	312	4125	3650	870
202	315/70R22.5	20	9.00	157/153	L	1076	312	4125	3650	870
203	315/80R22.5	20	9.00	157/153	L	1076	312	4125	3650	870
205	11R22.5	16	8.25	146/143	M	1050	279	3000	2725	830
	11R24.5	16	8.25	149/146	L	1104	279	3250	3000	830
	205/75R17.5	14	6.00	124/122	M	753	204	1600	1500	750
	215/75R17.5	14	6.00	126/124	M	767	211	1650	1500	760
	225/70R19.5	14	6.75	128/126	M	811	226	1800	1700	760
	235/75R17.5	16	6.75	132/129	M	797	233	2000	1850	830
	255/70R22.5	16	7.50	140/137	M	930	255	2500	2300	830
	265/70R19.5	16	7.50	140/138	M	867	262	2500	2360	830
	275/70R22.5	18	8.25	148/145	M	958	276	3150	2900	900
	285/75R24.5	16	8.25	147/144	L	1050	283	3070	2800	830
	295/75R22.5	16	9.00	146/143	L	1014	298	3000	2725	830



206

High wear resistance.
High cost performance.
Excellent fuel efficiency.



207

Good abrasion resistance, anti-puncture character.
Excellent traction performance.
Deepened groove design.



208

TMS technology and special compound for smooth tread wear.
Special pattern design provides good anti-eccentric wear.
Block tread.



209

Super abrasion resistance, excellent heat dissipation.
Good handling and traction, with higher original mileage.
Excellent fuel efficiency.



216

Enhanced superior adhesion properties of the ground.
Excellent wet skid resistance.
Special tread design provides a low heating up.



218

Heavy duty radial truck tire

www.roogootire.com



Excellent load capacity and super abrasion resistance.
Good tear resistance and wear resistance.



219

High wear resistance.
Excellent anti-side skid character and good drainage.
Good handling quality.



228

Strong traction and breaking power.
Enhanced load ability
Excellent abrasion resistance.



258

Four straight groove can provide excellent braking and driving performances.



268

Super abrasion resistance, excellent heat dissipation.
Good handling and traction, with higher original mileage.
Excellent fuel efficiency.

ROOGOO

Pattern	Size	PR	Standard rim	Load index	Speed rating	Overall diameter mm	Section width mm	Max Load(kg)		Pressure kpa
								Single	Dual	
206	7.50R16	14	6.00G	122/118	L	805	215	1500	1320	770
	9.5R17.5	18	6.75	143/141	M	974	229	2725	2575	875
207	11R22.5	16	8.25	146/143	M	1050	279	3000	2725	830
	11R24.5	16	8.25	149/146	L	1104	279	3250	3000	830
208	11R22.5	16	8.25	146/143	M	1050	279	3000	2725	830
	11R24.5	16	8.25	149/146	L	1104	279	3250	3000	830
	285/75R24.5	16	8.25	147/144	L	1050	283	3070	2800	830
	295/75R22.5	16	9.00	146/143	L	1014	298	3000	2725	830
209	385/65R22.5	20	11.75	160	K	1072	389	4500	4250	900
216	12.00R24	20	8.50	160/157	K	1226	313	4500	4125	900
218	9.00R20	16	7.00	144/142	K	1018	258	2800	2650	900
	10.00R20	18	7.50	149/146	K	1052	275	3250	3000	930
	11.00R20	18	8.00	152/149	K	1082	296	3550	3250	930
	12.00R20	20	8.50	156/153	M	1122	313	4000	3650	900
219	11R22.5	14	8.25	144/142	M	1050	279	2800	2650	830
	11R24.5	14	8.25	146/143	M	1104	279	3000	2725	830
	285/75R24.5	14	8.25	144/141	M	1050	283	2800	2575	830
	295/75R22.5	14	9.00	144/141	M	1014	298	2800	2575	830
	12.00R24	20	8.50	160/157	K	1226	313	4500	4125	900
228	12.00R24	20	8.50	160/157	K	1226	313	4500	4125	900
258	11.00R20	18	8.00	152/149	K	1085	296	3550	3250	930
268	6.50R16LT	12	5.50F	110/105	K	750	185	1060	925	670
	7.00R16LT	14	5.50F	118/114	K	775	205	1320	1180	770
	7.50R16LT	14	6.00G	122/118	L	805	215	1500	1320	770
	8.25R16LT	16	6.50H	128/124	L	855	235	1800	1600	770
	8.25R20	16	6.50	139/137	K	974	236	2430	2300	930
	9.00R20	16	7.00	144/142	K	1018	258	2800	2650	900
	10.00R20	18	7.50	149/146	K	1052	275	3250	3000	930
	11.00R20	18	8.00	152/149	K	1082	296	3550	3250	930
	11R22.5	16	8.25	146/143	M	1050	279	3000	2725	830
	12.00R20	20	8.50	156/153	K	1122	313	4000	3650	900
	12.00R24	20	8.50	160/157	K	1226	313	4500	4125	900
	12R22.5	18	9.00	152/149	M	1084	300	3550	3250	930
	13R22.5	18	9.00	154/151	L	1124	320	3750	3450	830
	315/80R22.5	18	9.00	154/151	M	1076	312	3750	3450	830
	315/80R22.5	20	9.00	157/153	L	1076	312	4125	3650	870

Tire Specifications

www.roogootire.com



259

Excellent braking and driving performances. Superior adhesion properties of the ground. Excellent wet skid resistance.



715

Superior driving performance. Good self-cleaning ability. Greater carrying capacity.



716

Excellent load capacity and super abrasion resistance. Good tear resistance. High wear resistance.



718

Excellent carrying capacity. Super wear-resistance and anti-puncture tread formulation.



725

Special designed mince pattern tire for harsh road provide higher mileage. The large lateral pattern block produce the driving forces, maintain excellent grip.



ROOGOO



801Q

Unique belt structure, with high wear-resistance and low producing heat crown formulation. Strong grip and wet-slip resistance performance.



918

Strong traction and braking power. Excellent self-cleaning performance. Reinforced puncture resistance and tear resistance.



918+

Tough belt construction, with high wear resistance and good impact force. Reinforced bead provide good traction.



928

Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage.

Pattern	Size	PR	Standard rim	Load index	Speed rating	Overall diameter	Section width	Max Load(kg)		Pressure
						mm	mm	Single	Dual	kpa
259	11.00R20	18	8.00	152/149	K	1082	296	3550	3250	930
715	9.00R20	16	7.00	144/142	K	1018	258	2800	2650	900
	10.00R20	18	7.50	149/146	K	1052	275	3250	3000	930
	11.00R20	18	8.00	152/149	K	1082	296	3550	3250	930
	12.00R20	20	8.50	156/153	M	1122	313	4000	3650	900
716	10.00R20	18	8.00	152/149	K	1085	296	3550	3250	930
	12R22.5	18	9.00	152/149	K	1084	300	3550	3250	930
718	12.00R20	20	8.50	156/153	M	1122	313	4000	3650	900
725	11.00R20	18	8.00	152/149	M	1080	296	3550	3250	930
	12.00R20	20	8.50	156/153	M	1122	313	4000	3650	900
801Q	10.00R20	18	7.50	149/146	K	1052	275	3250	3000	930
	11.00R20	18	8.00	152/149	K	1082	296	3550	3250	930
	12.00R20	20	8.50	156/153	M	1122	313	4000	3650	900
	13R22.5	18	9.75	154/151	L	1124	320	3750	3450	850
918	12.00R24	20	8.50	160/157	K	1226	313	4500	4125	900
	11.00R20	18	8.00	152/149	K	1085	296	3550	3250	930
	12.00R20	20	8.50	154/151	K	1122	313	3750	3450	830
	7.50R16	14	6.00G	122/118	L	805	215	1500	1320	770
	8.25R16	16	6.50H	128/124	L	855	235	1800	1600	770
918+	10.00R20	18	7.50	149/146	K	1052	275	3250	3000	930
928	9.5R17.5	18	6.75	143/141	J	842	240	2725	2575	875
	215/75R17.5	14	6.00	126/124	M	767	211	1700	1600	700
	225/70R19.5	14	6.75	128/126	M	811	226	1800	1700	760
	235/75R17.5	16	6.75	132/129	M	797	233	2000	1850	830
	265/70R19.5	16	7.50	140/138	M	867	262	2500	2360	830
	275/70R22.5	18	8.25	148/145	M	958	276	3150	2900	900
	295/75R22.5	16	9.00	146/143	L	1014	298	3000	2725	830
	315/80R22.5	20	9.00	156/150	K	1076	312	4000	3350	830